


- ① LINK BOX
- ② EARTHING BUS BAR
- ③ C.B. LINKS
- ④ DISCONNECTABLE S.A.
- ⑤ COAX BONDING CABLE
- ⑥ EARTHING CABLE
- ⑦ BNC CONNECTOR
- ⑧ PD SENSOR

LIST OF MAIN PARTS

Item	Name of parts	Materials
1	CABINET (2 mm)	STAINLESS STEEL
2	SURGE ARRESTER	ZnO
3	SUPPORT INSULATORS	EPOXY
4	GLAND FOR COAXIAL CABLE	STAINLESS STEEL
5	GLAND FOR EARTHING CABLE	STAINLESS STEEL
6	FIXING CLAMP	TINNED COPPER
7	CABLE END FIXING CLAMP	TINNED COPPER
8	BUS BARS(10x40)	TINNED COPPER
9	DISCONNECTABLE CROSSING BAR(10x40)	TINNED COPPER
10	EARTHING BAR BRIDGE TYPE(10x40)	TINNED COPPER
11	PROTECTION COVER	PLEXYGLASS
12	BOX EARTHING BAR	STAINLESS STEEL
13	BLOCKING ROD OF INCORRECT POS.	POLIAMIDE
14	HEAT SHRINKABLE TUBE	MWTD
15	PADLOCK FACILITY	STAINLESS STEEL
16	DOOR FIXING BOLTS	STAINLESS STEEL
17	GLAND FOR PD SENSOR CABLE(Ø21.3)	STAINLESS STEEL
18	PD SENSOR(CT35) AND BNC CABLE	
19	ADDITIONAL HOUSING AND COVER	STAINLESS STEEL
20	COVER (3 mm)	STAINLESS STEEL

CT/BIC COUPLER TERMINATION BOX



Specifications	
Protection degree	IP68
DC Voltage test	25 kV-5 min.
Short circuit test	50 kA-1 sec.
Internal power arcing	40 kA-0,1 sec.
Impulse voltage between parts	60 kV
Impulse voltage against earth	40 kV
*SA rate (Palitek-PMSP)	up to 10 kV
Bonding cable (Coaxial)	95-400 mm ²
**Inner Core Insulation Dia.(Min.-Max.)	Ø20-Ø36
**Screen Wires Dia.(Min.-Max.)	Ø25-Ø48
**Outer Dia.(Min.-Max.)	Ø30-Ø64
Weight	app. 81 Kg.
Volume of Filling compound (optional)	app. 57 Lt.
Colour	RAL 7032

PD-sensor for PD monitoring or temporary for HV commissioning test

*Indicate, if different SA (SVLs) required...
**Indicate, if bonding cable different size...

Rev.	Date	Drawn	Check	Apprv.	
01	12.01.15	AKARABUDAK	SERDENIZ	SERDENIZ	ADDITIONAL HOUSING AND COVER FOR PD MONITORING ON THE LINK BOX

Cross Bonding Link Box 15.01.01 Rev. 01
FOR UNDERGROUND TYPE
TYPE :LB.U.PD.CB.3SA.3.1

Drawn : 02.01.2015 / A.K.
 Approved : 02.01.2015 / S.E.