Brugg Cables High Voltage Accessories. Swiss solutions for independent applications.



BRUGG





E: info@cablegrid.com.au W: www.cablegrid.com.au

Fact Book High Voltage Accessories Brugg Cables Business Unit High Voltage Accessories Dr. Ruben Vogelsang Head of Product and Technology Management 2010 © Brugg Cables

Brugg Cables -	- products and services of the Business Unit High Voltage Accessories	3
Ir	ntroduction	5
	Dear customer	5
	Brugg Cables – reliable technology made in Switzerland	6
High voltage a	ccsessories for polymer cables	7
Т	erminations for polymer cables	9
	Design of a termination for polymer cables	9
	General	10
	Outdoor terminations with porcelain insulator for polymer cables	11
	Outdoor terminations with composite insulator for polymer cables	12
	GIS terminations for polymer cables	13
	Dry type plug-in terminations for polymer cables	14
	Transformer terminations for polymer cables	15
J	oints for polymer cables	16
	Design of a joint for polymer cables	16
	General	17
	Slip-on joints for polymer cables up to 72.5 kV	19
	Slip-on joints for polymer cables up to 145 kV	20
	Slip-on joints for polymer cables up to 1/0 kV	21
	Slip-on joints for polymer cables up to 245 kV	22
	Slip-on joints for polymer cables up to 550 kV	23
High voltage a	ccessories for oil-filled cables	25
Т	erminations for oil-filled cables	27
	Design of a termination for oil-filled cables	27
	General	28
	Outdoor terminations with porcelain insulator for oil-filled cables	29
	Outdoor terminations with composite insulator for oil-filled cables	30
	GIS terminations for oil-filled cables	31
	Iransformer terminations for oil-filled cables	32
J	OINTS FOR OIL-TILIED CADIES	33
	Design of a joint for oil-filled cables	33
	General Straight through jointe for ail filled aphlog	34
	Straight-infough joints for oil-filled cables	30 27
	Stop joints for on-fined cables	57
High voltage a	ccessories for polymer and oil-filled cables	39
Т	ransition joints	41
	Design of a transition joint	41
	General	42
	Transition joints for polymer and oil-filled cables	43
Additional equ	ipment	45
E	arthing equipment	47
_	General information	47
	Earthing- and Cross-bonding boxes	48
Т	ools	49
	Tools	49



General information	51
Our standards and services for reliable products	53
Our basis – advanced technology combining experiences with innovations	53
The basis of our quality – production at high standards	54
The guarantee for our quality – fully tested equipment	55
Quality beyond the factory – installation services	56
We offer more – after sales services, monitoring and diagnostics	57
Our know-how and experiences for your success – The Brugg Cables Academy	58
Our Experience for your success	59
Brugg – a history of experiences in cable systems	59
References I	60
References II	61
Brugg markets – worldwide and close to you	62



Brugg Cables – products and services of the Business Unit High Voltage Accessories

Dear customer

Thanks to your support, we've already succeeded in delivering over 40 000 accessories. The success of these products, which today covers a voltage range of 60 kV to 550 kV, enables us to provide consistent and reliable energy supplies on all five continents – day and night. We go beyond providing our customers with products of the highest Swiss quality. Our considerable experience within the global market allows us to deliver tailormade products and, ultimately, electrical energy into millions of households. With your help, we've been able to create an effective and communicative business. This success is felt daily and makes our work all the more enjoyable.

So why do our products work so well? They're simple to produce and install, easy to connect, compatible with all types of energy cables and can cope with the wide range of defects and inconsistencies occurring in energy network systems. We welcome challenging projects and excel in finding solutions for those of a difficult or complex nature – technical, climatic or cultural. So don't hesitate to contact us. We're here to realise your project; simply, efficiently and to your outmost satisfaction. We'd like to express our appreciation and thanks for your constant support and assistance in the continual improvement of our products and services, and hope that you will continue to accompany us now and into the future.

Yours sincerely,

Patrick Frei

Head of Business Unit High Voltage Accessories.



Patrick Frei



Brugg Cables – reliable technology made in Switzerland

A company that is known throughout the world for quality products and solutions.

Brugg Cables' excellent track record

For more than 100 years, Brugg Cables has been a valued partner within the fields of power industry and utilities.We are wellknown throughout the world for products and solutions that ensure long-lasting and reliable energy supplies.

Specialised business units

Brugg Cables is a member of the BRUGG Group and has its core business in the cable and cable-related industry. We combine innovations and experiences in the specialised business units of Telecom, Industry, Security, High Voltage Systems, High Voltage Accessories, Power Cables (Medium and Low Voltage Products) and Compound.

Bundled activities centralised at Brugg

We maintain a high standard of quality in our products and services by concentrating the relevant tasks of Strategy, Research & Development, Production and Testing at our headquarters in Brugg, Switzerland.

Wide range of well-balanced products

Our customers profit from a wide range of products from complete cable systems of any type to single cables or accessories. To ensure a highly reliable system, we focus on excellent quality in all our products and services. Thus, our accessories work excellently with cables of other manufacturers throughout the world.

All accessory products for your cable system

The business unit High Voltage Accessories provides everything you need for high voltage cables:

- Joints of any kind
- Terminations of any kind
- Additional equipment, such as earthing boxes, cable clamps or oil expansion tanks
- Installation services
- Tools of any kind



Headquarters of Brugg Cables



High voltage accsessories for polymer cables

Design of a termination for polymer cables





General

Our terminations for polymer cables are designed to be used independently of any type of polymer cable or cable manufacturer from 72.5 to 550 kV and up to a conductor cross-section of 2500 mm².

Termination design

Terminations for polymer cables consist of a stress cone with the deflector, an insulating compound, an insulator, a corona shield and a terminal stud.

Outstanding properties of the SiR stress cone

Stress cones are pre-moulded sleeves, which ensure field grading between the outer semiconducting layer and the insulation. Made of silicone rubber (SiR), they combine outstanding electrical and mechanical properties with excellent interface behaviour.

The electrical properties are designed to minimise stress, whilst mechanical properties ensure an optimum level of surface pressure on the cable which remains constant throughout the lifetime of the termination.

The deflectors are made of solid semiconducting material. Although costly, this ensures that they function properly at all voltage loads and guarantees a long and reliable lifetime. For optimum electrical stress distribution, the stress cones are designed with the help of computer simulations.

Quality in production and testing for reliable devices

Our stress cones are one-piece and fabricated in-house in an extremely clean surrounding. To ensure best quality, the fabrication is made with computerised machines. For zero failure production, every part is tested several times in the fabrication process. The stress cones must pass a final acceptance test. Each device is certified individually. This ensures that every stress cone leaving our factory is 100% reliable.

At a glance, the main advantages of the prefabricated and pretested SiR stress cones are:

page 10

- Very high breakdown strength of >23 kV/mm at 50/60 Hz
- Excellent temperature stability of between -50 and +180°C
- Very high life exponent of n >>40
- Excellent field grading performance at high frequency with deflectors of solid material
- Optimum electrical stress distribution due to computer-based design
- Zero failure guarantee with final high voltage pretesting
- Void-free contact pressure on the cable surface at normal and elevated load conditions due to excellent elasticity of the SiR
- Easy installation due to excellent mechanical properties and elasticity, no high mechanical forces needed

Five types of terminations for your applications

Five different types of terminations are available. For outdoor applications we offer terminations with porcelain and composite insulators. Each type of termination has a specific insulating compound, which can be chosen according to customer specifications – oil or SF₆ gas.

Terminations for transformers are made of cast epoxy resin insulators and can also be filled with silicone oil or SF₆ gas. For gas insulated switchgears (GIS), we offer two different types of terminations, traditional terminations and dry type plug-in terminations.

Our terminations for polymer cables are:

- Outdoor terminations with porcelain insulators
- Outdoor terminations with composite insulators
- Traditional GIS terminations
- Dry type plug-in GIS terminations
- Transformer Terminations



Outdoor terminations with porcelain insulator for polymer cables

Porcelain insulators have the longest tradition.

Their main advantages are:

- Excellent resistance against ultraviolet (UV) radiation
- Resistant against bird-picking
- Excellent track record in numerous countries and climate zones
- In service for more than 40 years at Brugg Cables with outstanding results

Terminations with porcelain insulators for polymer cables profit from the outstanding properties of our prefabricated, one-piece and pretested SiR slip-on stress cones.

The creepage distance of the insulators can be determined according to the application, the specifications of the customer or the necessities of different climate zones.

All terminations are designed and tested according to international standards, such as IEC 60840 (≤ 170 kV), IEC 62067 (> 170 kV), IEC 60815 (insulators), IEC 60071 (insulation coor-

dination) or IEEE Std 48-1996. Profit from the advantages of our outdoor terminations with porcelain insulators. All our terminations with porcelain insulators are designed to be used independently of any type of polymer cable or cable manufacturer from 72.5 to 550 kV and up to a conductor cross-section of 2500 mm².



Technical data of outdoor terminations with porcelain insulators for polymer cables

Operating voltage	Max. conductor cross-section (Cu/Al)	Ø over XLPE insulation	Max. Ø of outer sheath	Туре	Creepage distance
U _{max} /kV	mm²	mm	mm		mm
72.5	2000	35 - 94	115	TE 1.72-01	2900
145	2500	57 - 110	150	TE 1.145-01	4700, 5950, 7290
170	2500	57 - 110	150	TE 1.170-01	5950, 7290
245	2500	76 - 110	150	TE 1.245-01	8800, 10000
300	2500	76 - 110	150	TE 1.300-01	8800, 10000
420	2500	76 - 115	170	TE 1.420-01	13020, 17500, 21000
550	2500	90 - 130	170	TE 1.550-01	17500, 21000



Outdoor terminations with composite insulator for polymer cables

Composite insulators have been in growing demand over the past decades.

Their main advantages are:

- Lightweight
- Easy to handle
- Resistant against ultraviolet (UV) radiation
- Excellent hydrophobic behaviour
- Explosion-proof
- Earthquake-proof
- Excellent track record in numerous countries and climate zones
- In service for more than 25 years at Brugg Cables with outstanding results

Terminations with composite insulators for polymer cables profit from the outstanding properties of the prefabricated, onepiece and pretested SiR slip-on stress cones.

The creepage distance of the insulators can be determined according to the application, the specifications of the customer or the necessities of different climate zones.

All terminations are designed and tested according to international standards, such as IEC 60840 (≤ 170 kV), IEC 62067 (> 170 kV), IEC 60071 (insulation coordination) or IEEE Std 48-1996.

Profit from the advantages of our outdoor terminations with composite insulators. All our terminations with composite insulators are designed to be used independently of any type of polymer cable or cable manufacturer from 72.5 to 550 kV and up to a conductor cross-section of 2500 mm².



Technical data of outdoor terminations with composite insulators for polymer cables

Operating voltage	Max. conductor cross-section (Cu/AI)	Ø over XLPE insulation	Max. Ø of outer sheath	Туре	Creepage distance
U _{max} /kV	mm²	mm	mm		mm
72.5	1000	35 - 68	115	FR 1.72-01	2400
145	1200	57 - 80	115	FR 1.145-01	4790
	2500	57 - 110	150	FR 1.145-02	3890, 5580
170	2500	57 - 110	150	FR 1.170-01	3890, 5580
245	2500	76 - 110	150	FR 1.245-01	5350, 7820
300	2500	76 - 110	150	FR 1.300-01	6570, 9800
420	2500	76 - 115	170	FR 1.420-01	14100, 16800
550	2500	90 - 130	170	FR 1.550-01	16800, 18700



GIS terminations for polymer cables

GIS terminations were developed for use in SF_6 -gas insulated switchgears (GIS). Made with a cast resin body, they are designed to fit perfectly into your GIS.

Their main advantages are:

- Lightweight
- Easy to handle
- Classical tried and tested design with high tolerances for cables and applications
- Excellent track record in numerous countries and climate zones
- In service for more than 30 years at Brugg Cables with outstanding results

GIS terminations for polymer cables profit from the outstanding properties of the prefabricated, one-piece and pretested SiR slip-on stress cones.

All terminations are designed and tested according to international standards, such as IEC 62271-209 (GIS standard), IEC 60840 (≤ 170 kV), IEC 60071 (insulation coordination) IEC 62067 (> 170 kV) or IEEE Std 48-1996.

Profit from the advantages of our GIS terminations for polymer cables. All our GIS terminations are designed to be used independently of any type of polymer cable or cable manufacturer from 72.5 to 550 kV and up to a conductor cross-section of 2500 mm².

Technical data of GIS terminations for polymer cables

Operating voltage	Max. conductor cross-section (Cu/Al)	Ø over XLPE insulation	Max. Ø of outer sheath	Туре	Creepage distance
U _{max} /kV	mm²	mm	mm		mm
72.5	1000	35 - 80	115	TF 1.72-01	500
145	1200	57 - 80	150	TF 1.170-11	690
	2500	80 - 110	150	TF 1.170-12	710
170	2500	57 - 110	150	TF 1.170-11	690, 710
245	2500	76 - 110	150	TF 1.245-11	900
300	2500	76 - 110	150	TF 1.300-11	300
420	2500	76 - 115	170	TF 1.420-11	1385
550	2500	90 - 130	170	TF 1.550-11	1385



Dry type plug-in terminations for polymer cables

Dry type plug-in terminations have been in growing demand over the past years. Free of any insulating oil, they are with a cast resin body and designed to fit perfectly into your GIS.

Their main advantages are:

- Lightweight
- Easy to handle
- Can be plugged into the GIS without need of additional work at the GIS itself (such as evacuation work at the GIS)
- Cable and termination can be installed independently of the erecting of the GIS

For dry type plug-in terminations, stress cones are very important for field grading, much more than for the traditional terminations. High quality stress cones are therefore vital if longterm reliability of the termination is to be achieved. The dry type plug-in terminations profit from the outstanding properties of the prefabricated, one-piece and pretested SiR slip-on stress cones of Brugg Cables.

A special feature of the dry type plug-in termination of Brugg Cables is their design, which allows them to fit into every type of GIS, independent of whether these were constructed according to the old- or new GIS standards. This gives you, our customer, even more flexibility in your application with our terminations.

All terminations are designed and tested according to international standards, such as IEC 62270-209 (GIS standard), IEC 60840 (≤ 170 kV), IEC 62067 (> 170 kV), IEC 60071 (insulation coordination) or IEEE Std 48-1996.

Profit from the advantages of our terminations for polymer cables. All our dry type plug-in GIS terminations are designed to be used independently of any type of polymer cable or cable manufacturer from 72.5 to 170 kV and up to a conductor cross-section of 2500 mm².

Technical data of dry type plug-in GIS terminations for polymer cables

Operating voltage	Max. conductor cross-section (Cu/AI)	Ø over XLPE insulation	Max. Ø of outer sheath	Туре
U _{max} /kV	mm ²	mm	mm	
170	2500	57 - 110	150	TFD 1.170-11





Transformer terminations for polymer cables

Transformer terminations have a cast resin body and are designed to fit perfectly into your transformer.

Their main advantages are:

- Lightweight
- Easy to handle
- Classical tried and tested design with high tolerances for cables and their application
- Excellent track record in numerous countries and climate zones
- In service for more than 30 years at Brugg Cables with outstanding results

Transformer terminations for polymer cables profit from the outstanding properties of the prefabricated, one-piece and pre-tested SiR slip-on stress cones.

All terminations are designed and tested according to international standards, such as IEC 60840 (≤ 170 kV), IEC 62067 (> 170 kV), IEC 60071 (insulation coordination) or IEEE Std 48-1996.

Please note that the corona shield for transformer terminations are designed according to customer specifications and must be ordered separately.

Profit from the advantages of our transformer terminations for polymer cables. All our transformer terminations are designed to be used independently of any type of polymer cable or cable manufacturer from 72.5 to 550 kV and up to a conductor cross-section of 2500 mm².

Technical data of transformer terminations for poymer cables

reonnou							
Operating voltage	Max. conductor cross-section (Cu/Al)	Ø over XLPE insulation	Max. Ø of outer sheath	Туре	Creepage distance		
U _{max} /kV	mm ²	mm	mm		mm		
72.5	1000	35 - 80	115	TT 1.72-01	500		
145	1200	57 - 80	150	TT 1.170-11	690		
	2500	80 - 110	150	TT 1.170-12	710		
170	2500	57 - 110	150	TT 1.170-11	690, 710		
245	2500	76 - 110	150	TT 1.245-11	900		
300	2500	76 - 110	150	TT 1.300-11	300		
420	2500	76 - 115	170	TT 1.420-11	1385		
550	2500	90 - 130	170	TT 1.550-11	1385		





Design of a joint for polymer cables





General

Our joints for polymer cables are designed to be used independently of any type of polymer cable or cable manufacturer from 72.5 to 550 kV and up to a conductor cross-section of 2500 mm².

Joint design

Joints for polymer cables consist of a conductor clamp, an insulation body with semiconductive deflectors and middle electrode, a moisture barrier, a mechanical protection and the connections of the outer conductor.

Variety of conductor clamps

Conductor clamps connect both conductor ends of the cable. Their main task is to ensure a low contact resistance during lifetime. Our joints are designed to suit all common types of conductor clamps. Due to their many advantages, such as being easy to apply, we recommend the use of screwed conductor clamps.

Outstanding properties of the SiR insulation body

The insulation body consists of semiconductive deflectors at both sides, a semiconductive middle electrode and the insulation compound. It ensures field grading between the semiconducting layers of the cable and the conductor clamp. Made of silicone rubber (SiR), the insulation body combines outstanding electrical and mechanical properties with excellent interface behaviour.

The electrical properties are designed to minimise stress, whilst mechanical properties ensure an optimum level of surface pressure on the cable. The optimum surface pressure remains constant throughout the lifetime of the joint. The field grading deflectors and middle electrode are made of solid semiconducting material. Although costly, this ensures that they function properly at all voltage loads and guarantees a long and reliable lifetime.

For optimum electrical stress distribution, the insulation body is designed with the help of computer simulations.

Quality in production and testing for failurefree devices

Our insulation bodies are one-piece and fabricated in-house in an extremely clean surrounding. To ensure best quality, the fabrication is made with computerised machines. For zero failure production, every part is tested several times in the fabrication process. The insulation bodies must pass a final acceptance test. Each device is certified individually. This ensures that every joint leaving our factory is 100% reliable.

At a glance, the main advantages of the prefabricated and pretested SiR stress cones are:

- \bullet Very high breakdown strength of >23 kV/mm at 50/60 Hz
- Excellent temperature stability of between -50 and +180°C
- Very high life exponent of >>40
- Excellent field grading performances at higher frequency with deflectors and middle electrode of solid material
- Optimised electrical stress distribution due to computerbased design
- Zero failure guarantee with final high voltage pretesting
- Void-free contact pressure on the cable surface at normal and elevated load conditions due to excellent elasticity of the SiR
- Easy to install due to excellent mechanical properties and elasticity, no high mechanical forces needed

100% moisture protection with metal shield

Our standard joints are equipped with a real transverse moisture barrier made of a metal shield. This gives 100% moisture protection to the joint and results in a prolonged lifetime, making it highly reliable. In its basic version, the barrier is a metal sheet. In the more sophisticated version, the moisture barrier is a metal tube.

Variety of designs for mechanical protection

High reliability and a long lifetime are further ensured by the first-rate mechanical protection of the joint. Suited to the diverse applications of the customer, we offer a wide variety of mechanical protection designs.

Basic protection is provided by a heat shrink cover. For a higher degree of protection, steel or copper (Cu) housing and/or a box of polyester can be chosen. This polyester protection box is filled with an insulating compound, giving excellent sealing to the joint.

The different designs of mechanical protection enable you to select the best technical and cost-efficient solution for your application.



Joints for polymer cables

Our protection designs for polymer cable joints are:

- Metal sheet with heat shrink cover
- Metal sheet with protection box
- Cu-tube with coating of high density polyethylene (HDPE coating)
- Cu-tube with protection box
- Steel housing
- Steel housing with protection box



Joints with Cu-tube and HDPE coating in a concrete tunnel

Joints with polyester protection box in a concrete pit



Joints with polyester protection box in a concrete tunnel

All joints are designed and tested according to international standards, such as IEC 60840 (\leq 150 kV), IEC 62067 (>150 kV) or IEEE Std 404-2000.

Their main advantages are:

- Very compact dimensions
- 100% failurefree pretested one-piece SiR slip-on bodies
- Total moisture barrier with standard use of metal sheet
- High variety in application with different types of mechanical protection design
- Easy to handle and fast and easy to install
- No preload needed during transport or storage due to design with SiR slip-on bodies
- Excellent track record in all environments, laying conditions and climate zones
- In service for more than 20 years at Brugg Cables with outstanding results



Profit from the advantages of our slip-on joints for polymer cables. All our joints for polymer cables are designed to be used independently of any type of polymer cable or cable manufacturer from 72.5 to 550 kV and up to a conductor cross-section of 2500 mm².





Slip-on joints for polymer cables up to 72.5 kV

Variety of joints for your individual application needs

To assist you in the selection of the appropriate type of joint for your application, we have compiled an application table as given below.

High flexibility in earthing

Earthing of our joints can be made according to customer specifications. All joints are designed so that direct- or indirect earthing, straight through connection or cross bonding can be realised.

Applications of joints for polymer cables

Туре	Radial moisture barrier	Mechanical pro- tection	Advantages	Application
MPAH	Metal sheet	Heat shrink cover	 Extremely compact dimensions Basic sealing against moisture Cost effective 	 For limited dimensions, such as small manholes In tunnels or concrete manholes without permanent water ingress
MPAP	Metal sheet	Protection box	 Good mechanical protection in different environments Total sealing against moisture 	 In all types of laying, such as in tunnels, concrete pits or directly buried installations In buried installations with humid soil
MPCC	Cu-tube	Cu-tube with HDPE coating	 Compact dimensions High degree of mechanical protection Total sealing against moisture 	 In all types of laying, such as in tunnels, concrete pits or directly buried installations In installations with permanent humidity or shallow water
MPCP	Cu-tube	Cu-tube and protection box	 Highest degree of mechanical protection Total sealing against moisture 	 In all types of laying, such as in tunnels, concrete pits or directly buried installations In installations with permanent humidity or shallow water

Types of earthing of joints for polymer cables

Туре	Screen connection	Application
-21	Straight through connection, insulated to ground	Direct connection of cable screen without cross bonding
-21sp	Straight through connection with direct or indirect earthing	Connection of cable screen to earthing link
-31	Screen interruption, insulated to ground for cross bonding	Cross bonding of cable screen at the joint

Operating voltage	Max. conductor cross-section (Cu/AI)	Ø over XLPE insulation	Max. Ø of outer sheath	Туре	Mechanical protection and radial moisture barrier
U _{max} /kV	mm²	mm	mm		
72.5	1000	46 - 101	155	MPAH 1.72-21/-31	Metal sheet with heat shrink cover
	2500	46 - 101	155	MPAP 1.72-21/-31	Metal sheet with polyester protection box
	2500	46 - 101	155	MPCC 1.72-21/-31	Cu-tube with HDPE coating
	2500	46 - 101	155	MPCP 1.72-21/-31	Cu-tube with protection box



Slip-on joints for polymer cables up to 145 kV

Variety of joints for your individual application needs

To assist you in the selection of the appropriate type of joint for your application, we have compiled an application table as given below.

High flexibility in earthing

Earthing of our joints can be made according to customer specifications. All joints are designed so that direct- or indirect earthing, straight through connection or cross bonding can be realised.

Applications of joints for polymer cables

Туре	Radial moisture barrier	Mechanical pro- tection	Advantages	Application
MPAH	Metal sheet	Heat shrink cover	 Extremely compact dimensions Basic sealing against moisture Cost effective 	 For limited dimensions, such as small manholes In tunnels or concrete manholes without permanent water ingress
MPAP	Metal sheet	Protection box	 Good mechanical protection in different environments Total sealing against moisture 	 In all types of laying, such as in tunnels, concrete pits or directly buried installations In buried installations with humid soil
MPCC	Cu-tube	Cu-tube with HDPE coating	 Compact dimensions High degree of mechanical protection Total sealing against moisture 	 In all types of laying, such as in tunnels, concrete pits or directly buried installations In installations with permanent humidity or shallow water
MPCP	Cu-tube	Cu-tube and protection box	 Highest degree of mechanical protection Total sealing against moisture 	 In all types of laying, such as in tunnels, concrete pits or directly buried installations In installations with permanent humidity or shallow water

Types of earthing of joints for polymer cables

Туре	Screen connection	Application
-21	Straight through connection, insulated to ground	Direct connection of cable screen without cross bonding
-21sp	Straight through connection with direct or indirect earthing	Connection of cable screen to earthing link
-31	Screen interruption, insulated to ground for cross bonding	Cross bonding of cable screen at the joint

Operating voltage	Max. conductor cross-section (Cu/AI)	Ø over XLPE insulation	Max. Ø of outer sheath	Туре	Mechanical protection and radial moisture barrier
U _{max} /kV	mm²	mm	mm		
145	2500	46 - 101	155	MPAH 1.145-21/-31	Metal sheet with heat shrink cover
	2500	46 - 101	155	MPAP 1.145-21/-31	Metal sheet with polyester protection box
	2500	46 - 101	155	MPCC 1.145-21/-31	Cu-tube with HDPE coating
	2500	46 - 101	155	MPCP 1.145-21/-31	Cu-tube with protection box



Slip-on joints for polymer cables up to 170 kV

Variety of joints for your individual application needs

To assist you in the selection of the appropriate type of joint for your application, we have compiled an application table as given below.

High flexibility in earthing

Earthing of our joints can be made according to customer specifications. All joints are designed so that direct- or indirect earthing, straight through connection or cross bonding can be realised.

Applications of joints for polymer cables

Туре	Radial moisture barrier	Mechanical pro- tection	Advantages	Application
MPP	Protection box	Protection box	 Good mechanical protection in different environments Good sealing against moisture 	 In all types of laying, such as in tunnels, concrete pits or directly buried installations In buried installations with humid soil
MP / MPCC	Cu-tube	Cu-tube with HDPE coating	 Compact dimensions High degree of mechanical protection Total sealing against moisture 	 In all types of laying, such as in tunnels, concrete pits or directly buried installations In installations with permanent humidity or shallow water

Types of earthing of joints for polymer cables

Туре	Screen connection	Application
-21	Straight through connection, insulated to ground	Direct connection of cable screen without cross bonding
-21sp	Straight through connection with direct or indirect earthing	Connection of cable screen to earthing link
-31	Screen interruption, insulated to ground for cross bonding	Cross bonding of cable screen at the joint

Operating voltage	Max. conductor cross-section (Cu/AI)	Ø over XLPE insulation	Max. Ø of outer sheath	Туре	Mechanical protection and radial moisture barrier
U _{max} /kV	mm²	mm	mm		
170	2500	56 - 113	150	MPP 1.170-21/-31	Polyester protection box
	2500	56 - 113	150	MPCC 1.170-21/-31	Cu-tube with HDPE coating



Slip-on joints for polymer cables up to 245 kV

Variety of joints for your individual application needs

To assist you in the selection of the appropriate type of joint for your application, we have compiled an application table as given below.

High flexibility in earthing

Earthing of our joints can be made according to customer specifications. All joints are designed so that direct- or indirect earthing, straight through connection or cross bonding can be realised.

Applications of joints for polymer cables

Туре	Radial moisture barrier	Mechanical pro- tection	Advantages	Application
MPCC	Cu-tube	Cu-tube with HDPE coating	 Compact dimensions High degree of mechanical protection Total sealing against moisture 	 In all types of laying, such as in tunnels, concrete pits or directly buried installations In installations with permanent humidity or shallow water
MPSP	Steel housing stainless steel	Steel housing and protec- tion box	 Highest degree of mechanical protection Total sealing against moisture 	 In all types of laying, such as in tunnels, concrete pits or directly buried installations In installations with permanent humidity or shallow water

Types of earthing of joints for polymer cables

Туре	Screen connection	Application
-21	Straight through connection, insulated to ground	Direct connection of cable screen without cross bonding
-21sp	Straight through connection with direct or indirect earthing	Connection of cable screen to earthing link
-31	Screen interruption, insulated to ground for cross bonding	Cross bonding of cable screen at the joint

Operating voltage	Max. conductor cross-section (Cu/AI)	Ø over XLPE insulation	Max. Ø of outer sheath	Туре	Mechanical protection and radial moisture barrier
U _{max} /kV	mm²	mm	mm		
245	2500	68 - 115	150	MPCC 1.245-21/-31	Cu-tube with HDPE coating
	2500	68 - 115	150	MPCP 1.245-21/31	Cu-tube with protection box
	2500	68 - 115	150	MPSP 1.245-21/-31	Steel housing with protection box



Slip-on joints for polymer cables up to 550 kV

Variety of joints for your individual application needs

To assist you in the selection of the appropriate type of joint for your application, we have compiled an application table as given below.

High flexibility in earthing

Earthing of our joints can be made according to customer specifications. All joints are designed so that direct- or indirect earthing, straight through connection or cross bonding can be realised.

Applications of joints for polymer cables

Туре	Radial moisture barrier	Mechanical pro- tection	Advantages	Application
MP / MPSP	Steel housing	Steel housing and protec- tion box	 Highest degree of mechanical protection Total sealing against moisture 	 In all types of laying, such as in tunnels, concrete pits or directly buried installations In installations with permanent humidity or shallow water

Types of earthing of joints for polymer cables

Туре	Screen connection	Application
-21	Straight through connection, insulated to ground	Direct connection of cable screen without cross bonding
-21sp	Straight through connection with direct or indirect earthing	Connection of cable screen to earthing link
-31	Screen interruption, insulated to ground for cross bonding	Cross bonding of cable screen at the joint

Operating voltage	Max. conductor cross-section (Cu/AI)	Ø over XLPE insulation	Max. Ø of outer sheath	Туре	Mechanical protection and radial moisture barrier
U _{max} /kV	mm²	mm	mm		
300	2500	68 - 115	150	MPSP 1.300-21/-31	Steel housing with protection box
420	2500	82 - 115	175	MPSP 1.420-21/-31	Steel housing with protection box
550	2500	100 -129	175	MPSP 1.550-21/-31	Steel housing with protection box



High voltage accessories for oil-filled cables

Design of a termination for oil-filled cables







General

Our terminations for oil-filled cables are designed to be used independently of any type of oil-filled cable or cable manufacturer from 72.5 to 420 kV and up to a conductor cross-section of 2500 mm².

Termination design

Terminations for oil-filled cables consist of a paper-taped stress cone, an insulating liquid, an insulator, a corona shield and a terminal stud.

Prefabricated stress cones

The prefabricated paper-taped stress cones are a tried and tested design that has been used for terminations of Brugg Cables for more than 75 years.

The main advantage of these products is that the coils for stress cones are prefabricated in a clean and dry environment at our factory.

After a high quality process of taping, drying and impregnation, the coils are stored and delivered in sealed and oil-filled con-

tainers. Consequently, the coils remain dry in any degree of humidity and oil-impregnated for the installation.

For the best solutions, our prefabricated stress cones are made according to customer specifications.

The advantages of the prefabricated design are:

- High degree of quality and reliability due to production of prefabricated paper-taped coils in a clean and dry environment
- Very good thermal stability of up to 85°C
- Excellent field grading performances at normal frequency and higher frequency load
- Can be applied under supervision of Brugg personnel
- Excellent track record in all environment, laying conditions and climate zones
- In service for more than 75 years at Brugg Cables with outstanding results

Four termination types available

Four types of terminations are available. For outdoor applications, we offer porcelain and composite insulators. Terminations for SF₆ gas insulated switchgears (GIS) or transformers are made of cast epoxy resin insulators. The insulating liquid for all oil-filled terminations is oil. The corona shield is designed to minimise electrical stress.

Our terminations for oil-filled cables are:

- Outdoor terminations with porcelain insulators
- Outdoor terminations with composite insulators
- GIS terminations
- Transformer terminations

All additional equipment available

We deliver all additional equipment required to operate an oilfilled cable system, such as oil expansion tanks or pressure control cabinets.

Future delivery assurance

Our track record reflects our degree of commitment to quality, reliability and service. This means that our customers can rely on us to deliver cables, accessories and all other equipment for oil-filled cable systems for many years to come.





Outdoor terminations with porcelain insulator for oil-filled cables

Porcelain insulators have the longest tradition.

Their main advantages are:

- Excellent resistance against ultraviolet (UV) radiation
- Resistant against bird-picking
- Excellent track record in numerous countries and climate zones
- In service for more than 75 years at Brugg Cables with outstanding results

Terminations with porcelain insulators for oil-filled cables profit from the tried and tested Brugg design of prefabricated papertaped coils.

The maximum design oil pressure of the termination is 10 bar. On specific customer demand, designs with higher pressure values can be supplied.

The creepage distance of the insulators can be determined according to the application, the specifications of the customer or the necessities of different climate zones.

All terminations are designed and tested according to international standards, such as IEC 60141-1 or IEC 60071 (insulation coordination).

Profit from the advantages of our outdoor terminations with porcelain insulators. All our terminations for oil-filled cables with porcelain insulators are designed to be used independently of any type of oil-filled cable or cable manufacturer from 72.5 to 420 kV and up to a conductor cross-section of 2500 mm².



Technical data of outdoor terminations with porcelain insulators for oil-filled cables

Operating voltage	Max. conductor cross-section (Cu/Al)	Туре	Creepage distance
U _{max} /kV	mm ²		mm
72.5	2000	OE 1.72-01	2900
145	2500	OE 1.145-01	4700, 5950, 7290
170	2500	OE 1.170-01	5950, 7290
245	2500	OE 1.245-01	8800, 10000
300	2500	OE 1.300-01	8800, 10000
420	2500	OE 1.420-01	13020, 17500



Outdoor terminations with composite insulator for oil-filled cables

Composite terminations for oil-filled cables are the latest development of Brugg Cables. Composite insulators have been in growing demand over the past decades.

Their main advantages are:

- Lightweight
- Easy to handle
- Resistant against ultraviolet (UV) radiation
- Excellent hydrophobic behaviour
- Explosion-proof
- Earthquake-proof
- Excellent track record in numerous countries and climate zones

Terminations with composite insulators for oil-filled cables profit from the outstanding properties of the tried and tested Brugg design of prefabricated paper-taped coils.

The maximum design oil pressure of the termination is 10 bar. On specific customer demand, designs with higher pressure values can be supplied.

The creepage distance of the insulators can be determined according to the application, the specifications of the customer or the necessities of different climate zones.

All terminations are designed and tested according to international standards, such as IEC 60141-1 or IEC 60071 (insulation coordination).

Profit from the advantages of our terminations with composite insulators. All our terminations for oil-filled cables with composite insulators are designed to be used independently of any type of oil-filled cable or cable manufacturer from 72.5 to 420 kV and up to a conductor cross-section of 2500 mm².



Technical data of outdoor terminations with composite insulators for oil-filled cables

Operating voltage	Max. conductor cross-section (Cu/AI)	Туре	Creepage distance
U _{max} /kV	mm ²		mm
72.5	1000	OFR 1.72-01	2400
145	1200	OFR 1.145-01	4790
	2500	OFR 1.145-02	3890, 5580
170	2500	OFR 1.170-01	3890, 5580
245	2500	OFR 1.245-01	5330, 7820
300	2500	OFR 1.300-01	6570, 9800



GIS terminations for oil-filled cables

GIS terminations were developed for use in SF_6 gas insulated switchgears (GIS). Made with a cast resin body, they are designed to fit perfectly into your GIS.

Their main advantages are:

- Lightweight
- Easy to handle
- Classical tried and tested design with high tolerances for cables and applications
- Excellent track record in numerous countries and climate zones
- In service for more than 50 years at Brugg Cables with outstanding results

GIS terminations for oil-filled cables profit from the tried and tested Brugg design of prefabricated paper-taped coils.

The maximum design oil pressure of the termination is 10 bar. On specific customer demand, designs with higher pressure values can be supplied.

All terminations are designed according to international standards, such as IEC 60141-1, IEC 62271-209 (GIS standard) or IEC 60071 (insulation coordination).

Profit from the advantages of our GIS terminations. All our GIS terminations for oil-filled cables are designed to be used independently of any type of oil-filled cable or cable manufacturer from 72.5 to 420 kV and up to a conductor cross-section of 2000 mm².

Technical data of GIS terminations for polymer cables

Operating voltage	Max. conductor cross-section (Cu/Al)	Туре	Creepage distance				
U _{max} /kV	mm ²		mm				
72.5	1000	OF 1.72-01	500				
145	1200	OF 1.170-11	690				
170	1200	OF 1.170-11	690				
	2000	OF 1.170-12	710				
245	2000	OF 1.245-11	900				
300	2000	OF 1.300-11	900				
420	2000	OF 1.420-11	1385				





BRUGG

Transformer terminations for oil-filled cables

Transformer terminations have a cast resin body and are designed to fit perfectly into your transformer.

Their main advantages are:

- Lightweight
- Easy to handle
- Classical tried and tested design with high tolerances for cables and applications
- Excellent track record in numerous countries and climate zones
- In service for more than 60 years at Brugg Cables with outstanding results

Transformer terminations for oil-filled cables profit from the tried and tested Brugg design of prefabricated paper-taped coils.

The maximum design oil pressure of the termination is 10 bar. On specific customer demand, designs with higher pressure values can be supplied.

All terminations are designed according to international standards, such as IEC 60141-1, IEC 62271-209 (GIS standard) or IEC 60071 (insulation coordination).

Please note that corona shields for transformer terminations are designed according to customer specifications and must be ordered separately.

Profit from the advantages of our transformer terminations. All our transformer terminations for oil-filled cables are designed to be used independently of any type of oil-filled cable or cable manufacturer from 72.5 to 420 kV and up to a conductor crosssection of 2500 mm².

Technical data of transformer terminations for oil-filled cables

Operating voltage	Max. conductor cross-section (Cu/Al)	Creepage distance				
U _{max} /kV	mm²		mm			
145	1200	OT 1.170-11	690			
170	1200	OT 1.170-11	690			
	2000	OT 1.170-11	710			
245	2000	OT 1.245-11	900			
300	2000	OT 1.300-11	900			
420	2000	OT 1.420-11	1385			





Design of a joint for oil-filled cables





page **34**

General

Our joints for oil-filled cables are designed to be used independently of any type of oil-filled cable or cable manufacturer from 72.5 to 420 kV and up to a conductor cross-section of 2500 mm².

Joint design

Joints for oil-filled cables consist of a conductor clamp, a papertaped insulation, a moisture barrier, a mechanical protection and an earthing link.

Variety of conductor clamps

Conductor clamps connect both conductor ends of the cable. Their main task is to ensure a low contact resistance during lifetime. Although all typical conductor clamps can be used, we recommend using pressed clamps for the conductor connection of joints for oil-filled cables.

Prefabricated coils

The prefabricated paper-taped coils are a tried and tested design that has been used for Brugg Cables joints for more than 50 years.

The main advantage is that the coils are stored and delivered in sealed and oil-filled containers.

Consequently, the coils remain dry in any degree of humidity and oil-impregnated for taping during installation.

The advantages of the paper-taped design are:

- High quality and reliability of the paper-taped coils
- Very good thermal stability of up to 85°C
- Excellent field grading performances at normal frequency and higher frequency load
- Can be applied under supervision of Brugg personnel
- Excellent track record in all environment, laying conditions and climate zones
- In service for more than 50 years at Brugg Cables with outstanding results

Our joints for oil-filled cables are:

- Straight-through joints
- Stop joints

All additional equipment available

We deliver all additional equipment that is needed to operate an oil-filled cable system, such as oil expansion tanks or pressure control cabinets.

Future delivery assurance

Our track record reflects our degree of commitment to quality, reliability and service. This means that our customers can rely on us to deliver cables, accessories and all other equipment for oil-filled cable systems for many years to come.

100% moisture protection with metal housing

Joints for oil-filled cables come with a standard metal housing. This acts as a radial moisture barrier. Together with the mechanical protection of the joint, it guarantees a prolonged lifetime, making it highly reliable.

Choice of mechanical protection design

The basic mechanical protection is provided by the metal housing. For additional protection, a box of polyester can be chosen. This polyester protection box is filled with an insulating compound giving excellent sealing to the joint.

Our protection designs for oil-filled cable joints are:

- Metal housing
- Metal housing and protection box



Straight-through joints for oil-filled cables

Variety of joints for your individual application needs

Drawing upon a wealth of technological experience, Brugg Cables offers a wide range of straight-through joints for oil-filled cables.

The prefabricated paper-taped coils are a tried and tested design which has been used for Brugg Cables joints for more than 50 years.

All joints are designed according to international standards, such as IEC 60141-1.

High flexibility in earthing

Earthing of joints can be made according to customer specifications. All joints are designed so that direct or indirect earthing, straight through connection or cross bonding can be realised.

Their main advantages are:

- Tried and tested design
- Total moisture barrier due to metal shield
- Available with different types of mechanical protection
- Can be applied under supervision of Brugg personnel
- Usable with a standard pressure of 10 bar, higher pressure values for special applications possible
- Excellent track record in different laying and climate zones
- In service for more than 50 years with outstanding results

Profit from the advantages of our joints for oil-filled cables. All our joints for oil-filled cables are designed to be used independently of any type of oil-filled cable or cable manufacturer from 72.5 to 420 kV and up to a conductor cross-section of 2000 mm².



Applications of straight-through joints for oil-filled cables

Туре	Radial mois- ture barrier	Mechanical pro- tection	Advantages	Application
OM01 or -11	Steel hous- ing	Steel housing	 High degree of mechanical pro- tection in different environments Total sealing against moisture penetration 	 In concrete tunnels or concrete pits In insulated formations
OM21 or -31	Steel hous- ing	Steel housing with protection box	 Highest degree of mechanical protection in different environ- ments Total sealing against moisture penetration 	 In all types of laying, such as in tunnels, concrete pits or buried installations In installations with permanent humidity or temporary flooding

Types of earthing of joints for oil-filled cable joints

Туре	Screen connection	Application
-21/-01	Straight through connection, either insulated to ground (-21) or not insulated to ground (-01)	Direct connection of cable screen without cross bonding
-21sp	Straight through connection with direct or indirect earthing, insulated to ground	t Connection of cable screen to earthing link
-31/-01	Screen interruption and interruption of metal housing for cross bonding, insulated to ground (-31) or not insulated to ground (-11)	Cross bonding of cable screen at the joint



Technical data of straight-through joints for oil-filled cables

Operating voltage	Max. conductor cross-section (Cu/Al)	Туре	Mechanical protection
U _{max} /kV	mm ²		
72.5	630	OM 1.72-01	Metal housing or Metal housing and protection box
	3 x 400	OM 3.72-01	Metal housing or Metal housing and protection box
145	1000	OM 1.145-01	Metal housing or Metal housing and protection box
	1000	OM 1.145-11	Metal housing or Metal housing and protection box
	1000	OM 1.145-21	Metal housing or Metal housing and protection box
	1000	OM 1.145-31	Metal housing or Metal housing and protection box
170	800	OM 1.170-01	Metal housing or Metal housing and protection box
	800	OM 1.170-11	Metal housing or Metal housing and protection box
	800	OM 1.170-21	Metal housing or Metal housing and protection box
	2000	OM 1.170-22	Metal housing or Metal housing and protection box
	800	OM 1.170-31	Metal housing or Metal housing and protection box
	2000	OM 1.170-32	Metal housing or Metal housing and protection box
245	2000	OM 1.245-21	Metal housing or Metal housing and protection box
	2000	OM 1.245-31	Metal housing or Metal housing and protection box
300	2000	OM 1.300-21	Metal housing or Metal housing and protection box
	2000	OM 1.300-31	Metal housing or Metal housing and protection box
420	2000	OM 1.420-01	Metal housing or Metal housing and protection box



Stop joints for oil-filled cables

Stop joints are used to limit the oil pressure of cables that have to overcome differences in height.

Brugg Cables draws on a wealth of technological experience when designing such joints.

All joints are designed according to international standards, such as IEC 60141-1.

Their main advantages are:

- Tried and tested design
- Total moisture barrier due to metal shield
- 100 % oil stop at the joint
- Usable with a standard pressure of 10 bar, higher pressure values for special applications possible

- Available with different types of outer mechanical protection
- Excellent track record in different surroundings and climate zones
- In service for more than 40 years with outstanding results

Profit from the advantages of our stop joints. All our stop joints are designed to be used independently of any type of oil-filled cable or cable manufacturer from 72.5 to 420 kV and up to a conductor cross-section of 2000 mm².

Applications of stop joints

,	allonio ol olop jo					
Туре		Description	Radial mois- ture barrier	Mechanical pro- tection	Advantages	Application
OS		Standard stop joint	Steel housing	Metal housing or Metal hous- ing and pro- tection box	 Highest degree of mechanical protection in different environments Total sealing against moisture penetration 	 In all types of laying, such as in tunnels, concrete or buried installations In installations with perma- nent humidity or temporary flooding
OSF		Stop joint with back-to- back design	Steel housing	Steel housing	 High degree of mechanical protection in different envi- ronments Total sealing against mois- ture penetration 	 In laying with concrete, such as in tunnels or con- crete pits In insulated formations

Technical data of stop joints

Joint	Operating voltage	Max. conductor cross-section (Cu/Al)	Туре	Mechanical protection	
	U _{max} /kV	mm ²			
Standard stop joint	170	1200	OS 1.170-11	Metal housing or Metal housing and protection box	
Standard stop joint	245	2000	OS 1.245-31	Metal housing or Metal housing and protection box	
Standard stop joint	300	2000	OS 1.245-31	Metal housing or Metal housing and protection box	
Stop joint with back-to- back design	420	2000	OSF 1.420-11	Metal housing or Metal housing and protection box	



High voltage accessories for polymer and oil-filled cables

Design of a transition joint





General

Our transition joints are designed to be used independently of any type of cable or cable manufacturer from 72.5 to 420 kV and up to a conductor cross-section of 2500 mm².

Joint design

Transition joints are used to connect polymer- with paper-insulated cables.

They consist of a conductor clamp, SiR stress cones with an insulator for the polymer cable side and paper-taped coils for the paper-insulated cable side. Transition joints are covered by a moisture and a mechanical protection, and have an earthing link.

Variety of conductor clamps

Conductor clamps connect both conductor ends of the cable. Their main task is to ensure a low contact resistance during lifetime.

Outstanding properties of the SiR stress cone and insulator of the polymer cable side

The stress cone and insulator of the polymer cable side are the same as those used for conventional GIS or transformer terminations. Thus, the transition joint profits from the well proven, prefabricated and pretested silicone slip-on stress cones of Brugg Cables.

The hydraulic oil-barrier is achieved with the epoxy insulator of the polymer cable side. All components within the insulator are completely separated and connected to an external stainless steel expansion tank.

Reliable technology of paper-taped coils for the oil-filled cable side

Stress cones for the paper-taped cable side are of the same reliable and qualitative design as those for paper-taped joints or terminations. Thus, the transition joints profit from the well proven, paper-taped coils of Brugg Cables.

Flexible application of Brugg transition joints

The main advantage of our transition joints is their excellent quality and enduring reliability. They can be installed independently of any type of low-pressure oil-filled (LPOF) or highpressure pipe type (HPPT) cable.

Designed for very high pressure values

Our transition joints can be designed for operating pressures up to 14 bar – hydraulic or pneumatic – and emergency pressures up to 24 bar. This is achieved by means of reinforced casing that can be individually designed according to customer specifications.

Single and three core transition joints

We offer two different types of transition joints, single core and three core transition joints.

Single core transition joints are used to connect single core polymer-insulated cables to different types of single core paperinsulated, or paper/polypropylene-insulated cables.

Three core transition joints are used to connect a three core polymer-insulated cable with three single core paper-insulated or paper/polypropylene-insulated cables.

Choice of mechanical protection design

A stainless steel casing covers the whole arrangement. This gives an electrical connection of the metallic sheath between both cables and ensures that moisture and a strong mechanical protection is maintained. For additional protection, a box of polyester can be chosen. The box is sealed with an insulating compound of epoxy type, giving excellent sealing to the joint.

High flexibility in earthing

Our transition joints can either be chosen with straight through connection or with screen interruption for cross-bonding.

Wealth of experiences

The prefabricated stress cone on the polymer cable side and the paper-taped stress cone on the oil-filled cable side are tried and tested designs, which have been used for these types of joints for more than 20 years.

Our protection designs for transition joints are:

- Steel housing
- Steel housing and protection box



Transition joints

Transition joints for polymer and oil-filled cables

Drawing upon a wealth of technological experience, Brugg Cables offers a wide range of transition joints.

Variety of joints for your individual application needs

Our joints are designed according to international standards, such as IEC 60141-1 or IEC 62271-209 (GIS standard).

Their main advantages are:

- Outstanding properties and hence reliability of the prefabricated and pretested slip-on stress cones at the polymer cable side
- Reliable technology of prefabricated paper-taped coils at the oil-filled cable side
- Total moisture barrier with steel housing
- 100% oil stop at the joint
- Usable with a design pressure of 10 bar
- Higher pressure values for special applications of up to 14 bar possible

Applications of transition joints

- Can be installed independently of any sort of oil in the LPOF or HPPT circuit
- Can be applied under supervision of Brugg personnel
- Excellent track record in different laying and climate zones
- In service for more than 20 years with outstanding results

Profit from the advantages of our transition joints. All our transition joints are designed to be used independently of any type of cable or cable manufacturer from 72.5 to 420 kV and up to a conductor cross-section of 2500 mm²



Туре	Radial mois- ture barrier	Mechanical protection	Advantages	Application	Earthing
TOS11/-12	Steel housing	Steel housing	 High degree of mechanical protection in different environments Total sealing against moisture penetration 	 In laying with concrete, such as in tunnels or con- crete pits In insulated formations 	Straight through connection, not insulated to ground
TOS31/-32	Steel housing	Steel housing with pro- tection box	 Highest degree of mechanical protection in different environments Total sealing against moisture penetration 	 In all types of laying, such as in tunnels, concrete or buried installations In installations with per- manent humidity or tem- porary flooding 	Straight through connection, insulated to ground

Technical data of transition joints

Operating voltage	Max. conductor cross-section (Cu/Al)	Ø over XLPE insula- tion	Max. Ø of outer sheath	Туре	Mechanical protection
U _{max} /kV	mm²	mm	mm		
72.5	1200	< 80	115	TOS 1.72-11	Steel housing
	1200	< 80	115	TOS 1.72-31	Steel housing with protection box
145	1000	56 - 80	115	TOS 1.145-11	Steel housing
	1000	56 - 80	115	TOS 1.145-31	Steel housing with protection box
	2000	56 - 110	150	TOS 1.145-12	Steel housing
	2000	56 - 110	150	TOS 1.145-32	Steel housing with protection box
170	1000	56 - 80	115	TOS 1.170-11	Steel housing
	1000	56 - 80	115	TOS 1.170-31	Steel housing with protection box
	2500	56 - 110	150	TOS 1.170-12	Steel housing
	2500	56 - 110	150	TOS 1.170-32	Steel housing with protection box
245	2000	70 - 117	150	TOS 1.245-11	Steel housing
	2000	70 - 117	150	TOS 1.245-31	Steel housing with protection box
300	2000	70 - 117	150	TOS 1.300-11	Steel housing
	2000	70 - 117	150	TOS 1.300-31	Steel housing with protection box
420	2500	80 - 117	160	TOS 1.420-11	Steel housing
	2500	80 - 117	160	TOS 1.420-31	Steel housing with protection box



Additional equipment

General information

As a partner for complete solutions, Brugg Cables delivers all additional accessories and equipment needed for the optimum functioning of your cable system.

All additional equipment from one source

Brugg Cables supplies all additional equipment for your cable system such as:

- Cable clamps
- Earthing equipment for terminations
- Earthing equipment for joints
- Expansion tanks and pressure control cabinets for oil-filled cables and accessories

All types of cable clamps

Cable clamps are necessary devices, as they fix the cable to encourage proper functioning during normal conditions and faults. We offer a wide range of cable clamps depending on the cable type, its application and surrounding.

If you require detailed information on these items, just contact our experts for a separate offer.

Wide range of necessary earthing equipment

We provide a wide range of earthing equipment as shown in the tables below. Choose from a variety of these earthing device applications for all accessories.

All equipment needed for oil-filled cable systems

Expansion tanks and pressure control cabinets belong to an oilfilled cable system and transition joints. They are designed according to your cable system. If you require a detailed list of these items, just contact our experts for a separate catalogue or offer.

And more

Should you need additional and/or other specialised equipment, our experts will be pleased to help.



Cable clamp



Single pole disconnecting link box with surge voltage arrestor



Three pole disconnecting link box



Cross-bonding box



Earthing- and Cross-bonding boxes

Disconnecting link boxes for all types of terminations

Туре	Application with surge arrestor	Drawing no.	IP degree	Remarks
Disconnecting link box		S 1345-4	54	Single pole
Disconnecting link box		S 1344-4	54	With disconnecting knife
Disconnecting link box		S 1419-4	54	With disconnecting knife
Disconnecting link box		S 1107-4	54	Three pole
Disconnecting link box		S 1167-4	54	Three pole
Disconnecting link box		S 1660-4	65	With disconnecting knife

Devices for earthing of outdoor terminations

Туре	Application with surge arrestor	Drawing no.
Disconnecting link		S 1264-4
Disconnecting link		S 1406-4
Surge voltage arrestor		S 1407-4
Disconnecting element		S 1408-4
Supporting insulator		S 1409-4

Devices for earthing of GIS and transformer terminations

Туре	Application with surge arrestor	Drawing no.	Remarks
Disconnecting element		S 1503-4	72.5 - 170 kV
Disconnecting element		S 1504-4	170 kV
Disconnecting element		S 1505-4	245 kV
Disconnecting element		S 1506-4	72.5 - 170 kV
Disconnecting element		S 1509-4	170 kV
Disconnecting element		S 1508-4	245 kV

Disconnecting link boxes for all joints

Туре	Cross bonding	Drawing no.	IP degree	Remarks
Disconnecting link box		S 1479-4	54	Three pole
Disconnecting link box		S 1431-4	68	Three pole
Disconnecting link box		S 1348-4	54	Three pole
Cross-bonding box		S 1599-4	54	Three pole
Cross-bonding box		S 1600-4	54	Three pole
Cross-bonding box		S 1601-4	68	Three pole

Oil expansion tanks

Туре	Drawing no.	Oil volume	Weight with oil
		I	kg
AG 2.5	S 1456-4	2.5	6
AG 5	S 1483-4	5.0	17
AG 8	S 1288-4	8.0	18



Tools

Tools

We provide you with all the necessary tools to guarantee quality installation.

Complete set of tools

In order to provide you with high quality installation, we offer the necessary tools for the installation of high voltage accessories. Our tools can be bought or rented.

If you require detailed information concerning these items, just contact our experts for a separate catalogue and offer.



Cutting and peeling device



Peeling and stripping tool



Press head of 60 t



General information

Our basis – advanced technology combining experiences with innovations

Products that ensure a long-lasting energy supply are the result of extensive research and development.

Research and development for products and production

Long-lasting reliable energy supplies are vital for our society. That's why, Brugg Cables is constantly investing in research and development (R&D) of products and production. The latest innovative technology is combined with the experience of more than 100 years. This fruitful combination is realised from the development of new materials and techniques, through to extensive tests and scientific surveys and on to the whole production process.

Products with excellent properties

Our extensive commitment is to R&D results for products with the best electrical, thermal, mechanical and chemical properties. This balanced design ensures that all our accessories are highly reliable and can be used for cables of any manufacturer. All products are well proven and tested before being introduced into the market and finally delivered to you.

High quality products through:

- Tests in our on-site materials laboratory
- Advanced material analysis and diagnostics technology
- Application of modern simulation tools
- Experienced staff
- On-site prototype factory for all types of parts concerning accessories, such as stress-grading parts, silicone parts etc.
- Intensive tests in our own high voltage laboratories
- Constant cooperation with universities and research laboratories



Microscopic inspection in the materials laboratory



Mechanical tests in the materials laboratory



Simulation of the electrical field in a joint body



High voltage laboratory at Brugg Cables



Quality is an attitude that influences every single production step.

Production for high reliability products

In order to ensure that your cable system operates reliably, we have made quality our priority. This dictates every single process step from the selection of raw materials, through to production and continuous testing.

The key components of high voltage accessories, the slip-on bodies and stress cones, are made in-house and by our experts. In order to ensure that the quality of these products remains constant, the production process of the SiR slip-on bodies and stress cones is fully automatic.

For zero failure production, our products are continuously tested after every production step.

The main advantages of our high-quality production are:

- Production of one-piece SiR slip-on bodies and stress cones in-house at our factory in Brugg, Switzerland
- Experienced experts
- Use of best materials
- Tests of procurement parts
- Automatic computer-based production
- Zero failure production due to single control of every component after each production step

Officially proven quality

Our constantly applied quality processes are confirmed and certified according to:

- Quality Management Certificate SN EN ISO 9001: 2000 (since 1986)
- Environmental Management Certificate SNENISO 14001: 1996



Production of silicon parts in a very clean surrounding



Single control of the surface of a SiR slip-on joint body after production



Clean surface in the SiR slip-on joint body



The guarantee for our quality – fully tested equipment

Testing is essential to us, guaranteeing high reliability products.

Tests for guaranteed quality

At Brugg Cables, all equipment is tested several times before being delivered to the customer. Our key tests at a glance are:

- Development tests at our high voltage laboratory
- **Type tests** for all accessories up to 550 kV according to IEC 60840, IEC 62067, IEEE Std 48-1996 and IEEE Std 404-2000.
- **Prequalification tests** for all accessories up to 550 kV according to IEC 62067
- **Routine tests** of all prefabricated silicone stress cones and slip-on bodies according to IEC 60840 and IEC 62067 in-house in a modern fully screened test room.

Development tests

All accessories have to pass several tests during their development. These development tests apply stresses far above those occurring during normal operating conditions. The extensive tests ensure reliable and long-lasting products and are carried out in-house at our high voltage laboratory.

Type tests

As a matter of course, our accessories have passed all relevant type tests in accordance with international standards, such as IEC 60840 or IEC 62067. The type test applies electrical and thermal loads as well as water ingress above those occurring during normal conditions and lasts for a period of 20 days. This is followed by a watertightness test. Type tests are carried out under the supervision of experts from independent test laboratories.

Prequalification tests

In addition to the above, the high voltage accessories of Brugg Cables must pass a prequalification test according to IEC 62067. This test requires one year of operation at cyclic temperature load and elevated voltages. Brugg accessories have successfully completed these tests up to a voltage of 420 kV and will soon extend this up to 550 kV.

Routine tests

All one-piece, prefabricated SiR slip-on bodies receive a final routine test in accordance with IEC 60840 and room IEC 62067. At a higher voltage load, the products are shown to be completely free of partial discharges. Our pass rate for these tests is set higher than required by the standards. The delivery of 100% quality products from our factory is guaranteed as every piece undergoes a final test and is certified individually.



Prequalification test of 550 kV equipment



Prequalification test of 220 kV equipment at an independant test laboratory



Preparation for a routine test of a SiR slip-on body at our fully screened routine test room



Quality beyond the factory – installation services

An optimum performance of your cable system from day one can be guaranteed by the use of our installation services.

High quality installation

The quality of installation is vital for the reliable running of your cable system.

In order to ensure top performance of our products in the field, Brugg Cables operates with its own installation department. This means that the installation of our accessories is carried out by specially trained personnel with extensive experience. Our installation services include:

- Polymer cables and accessories up to 550 kV
- Oil-filled cables and accessories up to 420 kV
- Transition joints up to 420 kV
- Underwater installations

Profit from our services with an economic solution suited to your needs. Our experts provide complete or supervised installation services.

In addition we also offer training courses for your teams. If you require detailed information about the courses, just contact our experts for a separate catalogue and offer.

The main advantages of our installation services are:

- Own installation department with well educated, trained, and experienced personnel
- Training of your installation teams
- Supervision of your teams
- Assembly-friendly installation sets
- · Full supply of all tools, either on sale or on rental basis
- Installation services that are independent of the cable manufacturer

Support in commissioning testing

We offer commissioning tests after installation at your request. This service is offered by working closely together with different specialised testing companies and institutes. All commissioning tests are carried out according to international standards, such as IEC 60840, IEC 63067 and IEC 60141.



Preparation of the conductor connection for a polymer joint



Assembling-friendly installation of a slip-on joint by "air cushion" method



Commissioning test on-site at 420 kV porcelain terminations in Germany



Well connected.

page **57**

We offer more – after sales services, monitoring and diagnostics

Our support goes beyond delivery and installation.

Customer service support

Our customer service is there for all questions concerning your cable and/or accessories project before, during and after installation. A team of engineers and specialists is available at Brugg Cables to provide you with the necessary help.

Should you be interested in any service, just contact our experts.

Monitoring and diagnostics support

Following a full system approach, we also offer you devices, tools and know-how for monitoring and diagnostics. We work closely together with different specialised companies and research institutes, enabling us to provide you with a wide range of monitoring and diagnostics services. This includes:

- Temperature monitoring
- Partial discharge (PD) measurement and monitoring
- Humidity measurement and monitoring
- Condition assessment of service-aged cable systems
- Measurement of all relevant cable data, such as insulating resistance, impedance, conductor resistance measurements etc.
- Failure localisation and repair

Wide range of other testing means

Brugg Cables offers a wide range of testing means, depending on your requirements. This is achieved by working closely together with different specialised testing companies and institutes. The tests include:

- AC and DC voltage tests
- Partial discharge measurements
- Hydraulic measurements on pressurised oil-filled cables and accessories

Should you be interested in any device or service, just contact our experts.



Preparation for PD measurements at terminations for a customer in Switzerland



PD measurement for a customer in South America



Temperature monitoring along a cable system



Our know-how and experiences for your success – The Brugg Cables Academy

Know-how is at the heart of all functioning industrial applications. That's why Brugg Cables offers its customers continued quality education. Profit from the Brugg Cables Academy.

Know-how and experiences available for your needs

Reliable and functioning cable systems are influenced by a number of factors. These may range from choosing the right design of cables and accessories, considering the influences of thermal load conditions, selecting the appropriate earthing design or posing the right questions concerning installation tests, monitoring and diagnostic tools.

Brugg Cables has extensive knowledge in all these fields and wants to share this with you, our customers, helping you to stay constantly "Well connected".

Five central topics of the Brugg Cables Academy

The target of our education program is to provide you with relevant knowledge within your specific field. Brugg Cables Academy supports your need for specialization by offering courses in five central topics, which are:

- High voltage oil cable systems
- High voltage polymeric cables
- High voltage accessories for polymeric cables
- Partial discharge measurements & monitoring
- Diagnostics for cable systems

Typical course participants include engineers and utility technicians as well as project managers or persons involved within the relevant fields.

Standard or individual courses according to your needs

Standard courses are held in Brugg, Switzerland each year; in an autumn session in October and in a spring session in March. Courses can also be taken individually. Customers decide whether the courses are held in Switzerland or in their home country. For more information, contact our personnel or apply at info.hvaccessories@brugg.com.



New facilities in Brugg, Switzerland, with the rooms of the Brugg Cables Academy



Annual engineering training course in Brugg



Education by one of our experts at a customer meeting



Brugg - a history of experiences in cable systems

The history of cable systems is closely related to the history of our company. For decades, Brugg has been a leading company in cables, accessories, equipment, and all products and services around cable systems.

- 1896 founded by Gottlieb Suhner, Brugg begins delivering cables and wires. First customers are major Swiss utilities.
- 1900 Swiss utilities place large orders for paper-insulated lead sheathed power cables by Brugg.
- 1918 Brugg begins delivering large quantities of communication and power cable systems to support the Swiss railway company "SBB" in its electrification.
- 1928 Brugg delivers and installs the first Swiss underwater cable across Lake Lugano.
- 1934 Brugg already delivers a 150 kV oil-filled cable allowing higher power transmission.
- 1942 4500 m long low-pressure oil-filled cable system is delivered and installed for a Swiss customer.
- 1955 Brugg is once again ready on the market, introducing its first cable with synthetic insulation at 20 kV, allowing its customers to make use of the advantages of polymer insulations.
- 1960 Brugg develops a 420 kV oil-filled cable system suited to increasing power demands.
- 1974 Brugg develops polymer joints for voltages up to 72.5 kV, coinciding with new requirements of long-distance cable systems and newly introduced polymer insulations.
- 1980s Brugg leads in the development of polymer cables and accessories of up to 220 kV, as power demands increase.
- 1997 Brugg delivers polymer cable systems of 420 kV, ensuring a powerful and reliable energy supply.
- 2008 Brugg develops a complete 550 kV polymer cable system with all types of terminations and joints suited to increasing power needs. Once again Brugg Cables places itself amongst the premier league of its field.
- 2010-1 New production and office facilities were opened in the center of Brugg. Beside the Business Unit High Voltage Accessories, also the board of the BRUGG-Group moved into the new facilities.
- 2010-2 Education towards its customers is brought to a new level. In the new facilities, the "Brugg Cables Academy" was founded, providing courses concerning all issues around cable systems. The first courses were held in October 2010 and were highly requested.



Production facilities of Brugg around 1900



Laying of 420 kV oil-filled cables in Switzerland in the 1960s



Product facilities at Brugg in the late 1970s



Brugg Cables' modern, fully screened test room for AC voltages up to 600 kV



New office and production facilities in Brugg and home of the "Brugg Cables Academy"



page **60**

References I

From the 75 years of delivering high voltage accessories, we have a reference list that is far too large to be listed here in detail.



Installation of joints in Abu Dhabi



Outdoor terminations with porcelain insulators in the USA



Outdoor terminations with composite insulators in Switzerland



Outdoor terminations with composite insulator in Brazil



Installation of transition joints in Germany



GIS-terminations of the highest voltage level (550 kV) in Egypt



References II

We are pleased that we could carry out projects that have lead to more than 40'000 references with different cable designs in all climate zones in 66 countries on 5 continents.



Transformer terminations in outdoor application in Jordan



Transformer terminations in indoor application in South Africa



Tests of outdoor terminations in Switzerland



Checking of delivery of transition joints in the USA



Discussion of technical details at a joint bay in Qatar

CABLES

Well connected.

BRUGG



Preparation for the installation of outdoor terminations in Norway

HIGH VOLTAGE ACCESSORIES

Phone +41 (0)56 460 3333 • Fax +41 (0)56 460 3536 • info.hvaccessories@brugg.com

Brugg markets - worldwide and close to you

In addition to our headquarters in Switzerland, we also have representatives in:

- Sozhou, Shanghai and Beijing, China
- Prague, Czech Republic
- Schwieberdingen (Stuttgart), Germany
- Milano, Italy
- Salmiya, Kuwait
- Dubai, United Arab Emirates
- Rome, GA, USA

Our main advantages are:

- Competent and local language speaking agents near you
- Delivery in all climate zones
- Delivery of accessories to all cable manufacturers



Worldwide representatives of Brugg Cables



For further information please contact us.



Our head office

Switzerland

Brugg Kabel AG Klosterzelgstrasse 28 CH-5201 Brugg Phone +41 (0)56 460 33 33 Fax +41 (0)56 460 35 36 info@brugg.com www.bruggcables.com

Sales infrastructure: Fax +41 (0)56 460 32 98 info.havaccessories@brugg.com

Our branches

Germany

Brugg Kabel GmbH Daimlerstrasse 8 DE-71701 Schwieberdingen Phone +49 7150 91635 0 Fax +49 7150 91635 55 info.de@brugg.com www.bruggcables.com

Italy

Brugg Cables Italia srl Via Palermo, 20 Sesto San Giovanni IT-20099 Milano Phone +39 02 22 47 00 48 Fax +39 02 24 86 28 93 info.it@brugg.com www.bruggcables.com

China

Brugg Cables (Shanghai) Co., Ltd. Building No.7 Sai Te Industrial Park No.1300 Jun Gong Road CN-Shanghai Phone +86 21 5506 2530 Fax +86 21 5506 2533 info@brugg-cables.com.cn www.brugg-cables.com.cn

Kuwait

Brugg Cables Salwa, Block 12 Street No 7, House No 76 Floor No 1, Flat No 1 P.O. Box 2191 KW-22022 Salmiya Phone +965 2566 32 71 Fax +965 2566 32 73 info.kw@brugg.com www.bruggcables.com

USA

Brugg Cables, LLC 25 Anderson Road P.O. Box 5231 US-Rome, GA 30162-5231 Phone +1 706 235 8755 Fax +1 706 235 7635 info.usa@brugg.com www.bruggcables.com

United Arab Emiraates

Brugg Cables, LLC P.O. Box 28896 AE-Dubai Phone +971 4 334 55 40 Fax +971 4 334 41 18 info.ae@brugg.com www.bruggcables.com

You will find further sales partners in your region on www.bruggcables.com. A company of the Brugg Group.

